

粘贴式密封条

Paste sealing strip

主要适用范围:

适用各种室内门上

安装方式:

自带胶, 直接粘贴即可,
背胶采用进口台湾 3M 或
台、德技术合作之高度压敏胶

产品特性:

减少关开门的撞击声, 防震
防止灰尘、臭气、蚊虫的透入
延长门的寿命, 减小噪音

Main application:

Suitable for all kinds of indoor

Installation method:

Installation method: 1 bring glue, paste directly,
Beijiao imported Taiwan 3M or Taiwan,
German technical cooperation of high pressure
sensitive adhesive

Product features:

To reduce the impact of the door open shock
Gum to prevent dust, odor, mosquito penetration
Extend the life of the door to reduce noise

密封条 - 粘贴式 Seal strip - Paste type



此密封条可一分为二, 撕开单独使用
This seal can be split in two and torn apart for use alone

安装效果图 Installation diagram



剖面图 Profile	型号 Item NO.	规格 Spec W*H*F	适用门缝 Applicable gap	适用的档口 Suitable stall	材质 Material	包装 米/件 Packing M/box
	Q1-11	9*3.5	2-3	9 以上	PVC	500
	Q1-12	11.8*5.5	2-4	12 以上	PVC 橡塑 阻燃	400
	HOT 畅销品 Q1-26	9*5	3-4	9 以上	橡塑共挤 Rubber co-extrusion	600
	HOT 畅销品 Q1-65	12*6	3-5	12 以上	PVC 橡塑 阻燃	200
	Q1-HH01	12*8	5-7	12 以上	PVC	200
	Q1-86	12*5	2-3	12 以上	橡塑	300
	Q1-64	10*2	2	10 以上	橡塑	500
	Q1-67	9*1.5	1.5	9 以上	橡塑	500
	HOT 畅销品 Q1-79 踢脚线专用	6.6*2	2	6.6 以上	橡塑共挤 Rubber co-extrusion	1600
	Q1-99	16*2	2	16 以上	橡塑	350

温馨提示

为获得更好的黏贴效果,
密封条必须粘贴在光滑、
清洁、干燥的表面

Tips: to achieve better adhesion effect,
the sealing strip must be pasted on a
smooth, clean, surface dry surface



现已采用软硬共挤的技术
使产品的粘性更牢固
Now the use of soft and hard co
extrusion technology to make the
product more adhesive

